

PARAMETRY TRAS – BIEG NA ORIENTACJĘ



	E1			E2			E3			E4			
kategoria	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	kategoria
K10N	6	2790*	50	5	2440*	50	6	2910*	70	5	2470*	50	K10N
K10	7	1720	45	8	1830	40	6	1640	60	7	1670	45	K10
K12	8	2250	50	10	2310	45	8	2390	65	10	2500	55	K12
K14	12	2990	60	13	2930	55	11	3690	80	10	2810	60	K14
K16	14	3320	65	14	3080	55	13	4560	90	14	3180	70	K16
K18	16	3500	70	14	3170	65	15	5170	95	18	3590	70	K18
K20	15	3600	75	16	3490	75	16	5620	95	17	3810	75	K20
K21	19	4420	100	20	4410	90	17	6460	110	17	4160	100	K21
K35	15	3590	80	14	3170	70	15	5470	90	17	3810	90	K35
K40	15	3590	80	14	3170	70	15	5470	90	17	3810	90	K40
K45	12	2980	75	12	2860	60	12	4300	85	14	2730	70	K45
K50	12	2980	75	12	2860	60	12	4300	85	14	2730	70	K50
K55	12	2710	70	11	2540	60	10	3520	70	11	2440	60	K55
K60	12	2710	70	11	2540	60	10	3520	70	11	2440	60	K60
K65+	9	1900	50	10	2010	40	9	3190	70	9	2260	55	K65+
Rodzinna	7	2150	50	10	1960	40	8	2600	55	10	2310	60	Rodzinna
Krótką	7	2150	50	10	1960	40	8	2600	55	10	2310	60	Krótką
Średnia	13	2790	70	12	2820	65	15	4290	80	14	3280	75	Średnia
Długą	15	3490	80	14	3560	80	14	5550	120	18	4140	95	Długą

*możliwość skrócenia trasy (parametry podane wzdłuż wstążek)

PARAMETRY TRAS – BIEG NA ORIENTACJĘ



	E1			E2			E3			E4			
kategoria	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	liczba PK	dystans [m]	Przewyższenie [m]	kategoria
M10N	6	2790*	50	5	2440*	50	6	2910*	70	5	2470*	50	M10N
M10	6	1980	50	8	1850	40	5	1730	60	6	1840	50	M10
M12	8	2180	55	11	2580	50	8	2710	75	10	2460	60	M12
M14	12	3070	65	14	2890	50	11	3940	85	11	2860	65	M14
M16	14	3340	75	16	3500	70	15	5700	90	16	3470	80	M16
M18	15	3790	90	15	3600	80	20	7210	110	17	3840	85	M18
M20	18	4130	95	17	3910	85	19	7480	130	18	3970	85	M20
M21	23	5520	115	23	5320	100	23	9220	160	22	5200	120	M21
M35	20	3960	90	15	3600	80	20	7490	120	18	3970	85	M35
M40	20	3960	90	15	3600	80	20	7490	120	18	3970	85	M40
M45	15	3390	80	14	3390	75	16	6170	105	16	3460	80	M45
M50	15	3390	80	14	3390	75	16	6170	105	16	3460	80	M50
M55	12	3030	70	13	3020	60	12	5270	80	13	3010	70	M55
M60	12	3030	70	13	3020	60	12	5270	80	13	3010	70	M60
M65	11	2490	60	11	2440	55	9	3830	70	10	2580	60	M65
M70	11	2490	60	11	2440	55	9	3830	70	10	2580	60	M70
M75+	9	1830	45	10	1870	40	8	3050	60	8	2090	50	M75+

*możliwość skrócenia trasy (parametry podane wzdłuż wstążek)